



# Best Towing Wheel in the Industry.

## Elastomeric High Tensile (EHT)

RWM's Elastomeric High Tensile (EHT) wheels are a molded rubber wheel. They are one of the best wheels for towing applications because the highest quality, high tensile premium rubber is bonded to a heavy-duty aluminum core that provides superior strength and longevity. The EHT wheel is rated up to 200% higher than conventional rubber wheels. This means the EHT rubber will not crack, chunk, dry out or de-bond from the core during heavy use. Whether it is indoor or outdoor environments, the EHT wheel will work well in the most vigorous towing applications. The special rubber compound is non-marking to floors and allows for use at a higher tow speed than other wheels. They are the ideal wheel for aerospace tooling, ground support, tire manufacturing and other industrial applications.

Wheel Diameter	Wheel Width	Capacity	Axle Diameter	Ball Bearing	Tapered Bearing	Hub Length	Approx Weight
4"	2"	700	1/2"	RAB-0420-08-EHT-NM		2-1/2"	1.6
5"	2"	800	1/2"	RAB-0520-08-EHT-NM		2-1/2"	2
6"	2"	820	1/2"	RAB-0620-08-EHT-NM		2-1/2"	2.7
	2"	1000	1/2"	RAB-0820-08-EHT-NM		2-1/2"	3.7
8"	3"	1500	3/4"	RAB-0830-12-EHT-NM	RAT-0830-12-EHT-NM	3-1/2"	8
	3"	1500	1"	RAB-0830-16-EHT-NM	RAT-0830-16-EHT-NM	3-1/2"	8
10"	3"	2000	3/4"	RAB-1030-12-EHT-NM	RAT-1030-12-EHT-NM	3-1/2"	10
	3"	2000	1"	RAB-1030-16-EHT-NM	RAT-1030-16-EHT-NM	3-1/2"	10
12"	3"	2280	3/4"	RAB-1230-12-EHT-NM	RAT-1230-12-EHT-NM	3-1/2"	14.5
	3"	2280	1"	RAB-1230-16-EHT-NM	RAT-1230-16-EHT-NM	3-1/2"	14.5
	3"	2280	1-1/4"		RAT-1230-20-EHT-NM	3-1/2"	14.5



1225 Isley Drive • Gastonia, NC 28052  
 Phone: 1-800-634-7704 • Fax: 1-800-253-6634

[www.rwmcasters.com](http://www.rwmcasters.com)  
[customerservice@rwmcasters.com](mailto:customerservice@rwmcasters.com)

**ENGINEERED TO OUTPERFORM**